

## Plastic 4-Knob Filter



## **FEATURES**

Low operating pressure drop

Reduced maintenance/downtime

Prolonged filter life

High throughput capacity

Helps eliminate abrasion

Custom design available

Applications: Steel Foundries Chemical Processing Industrial Boilers Food Processing Asphalt Production

Pleated Bag Cap Option	Core Option
Galvanized- top & bottom	
304SS - top and bottom end cap	optional
Metal helix	inner core standard
Galvanized perforated	inner core optional

I	Media Options				
I	CF 11SB	100% polyester spunbond			
	CF 11SB-HO	100% polyester spunbond with hydroeleophobic finish			
	CF 11SB-ME	100% polyester spunbond with aluminized anti-static finish			
	CF 12FR	Cellulose/polyester with fire-retardant finish			
	CF 15FR	Blended paper media with nano fiber and fire-retardant finish			
Ι	CF 16SB-TX	100% spunbond with ePTFE membrane			

Overall Length	Media Area Pleats				
20.05 in.	24 ft <sup>2</sup>				
34.625 in.	43 ft <sup>2</sup>				
40 in.		71 ft²	50 ft <sup>2</sup>	156 ft²	115 ft <sup>2</sup>
55 in.	60 Pleats	65 Pleats	70 Pleats	145 Pleats	160 Pleats

8401 Air Commerce Drive, Louisville KY 40219 | toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364 info@kochfilter.com | www.kochfilter.com

## Plastic 4-Knob Filter

Koch Filter offers a complete line of pleated bag filters designed to fit Nederman<sup>®</sup> style Uniclean Cartridges.