

SprayStop[™] S, SHC & HCX

Standard, High & Super High Capacity Overspray Media



Features

- Stack protection and emissions control for a wide range of coating materials.
- Available in pads, blankets and rolls.
- Excellent paint-holding capacity on high solids.
- Exceptional value for high volume coating operations.
- Full depth loading. Exclusive design allows paint solids to permeate the blanket from back to front.

SprayStop Polyester Media are designed with multiple fibers and layers to be used in paint overspray applications where process control requires long filter service life, maximum efficiency and air flow, while ensuring maximum production capability.

Applications

- Aerospace
- Furniture Manufacturing
- Automotive Manufacturing
- Appliance Manufacturing
- Automotive Aftermarket
- Contract Coaters

Performance Data

| | SprayStop S | SprayStop SHC | SprayStop HCX |
|----------------------------|-------------|---------------|---------------|
| Part No. Series | 540 | 541 | 539 |
| Media Thickness | 1" | 1" | 1.50" |
| Test Air Flow FPM | 150 | 150 | 150 |
| Initial Resistance on w.g. | .08" | .07" | .03" |
| Paint Holding Capacity | 1478 GM | 1677 GM | 2628 GM |
| Rated Removal Efficiency | 99.52% | 99.73% | 99.33% |

All information provided from current 40 CFR PART 63 NATIONAL EMISSION STANDARD "6H" Testing.



| Paint Type | SprayStop S | SprayStop SHC | SprayStop HCX |
|------------------------|-------------|---------------|---------------|
| Air dry Enamels | GOOD | BEST | BETTER |
| Stain | GOOD | BEST | BETTER |
| Lacquers | GOOD | BEST | BETTER |
| Primers | GOOD | BEST | BETTER |
| E/S Adhesion Promoters | GOOD | BEST | BETTER |
| Waterbase | GOOD | BEST | BETTER |
| Sealers | GOOD | BETTER | BEST |
| Bake Enamels | GOOD | BETTER | BEST |
| High Solids | GOOD | BETTER | BEST |
| Clear Coats | GOOD | BETTER | BEST |
| Gel Coats | GOOD | BETTER | BEST |
| Adhesives | GOOD | BETTER | BEST |



KOCH FILTER
PURE PERFORMANCE

8401 Air Commerce Drive, Louisville, KY 40219
 toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364
 info@kochfilter.com | www.kochfilter.com