

SprayStop™ S, SHC & HCX

Standard, High & Super High Capacity Overspray Media



SprayStop S

SprayStop HCX

SprayStop SHC

Features

- Stack protection and emissions control for a wide range of coating materials.
- Available in pads, blankets and rolls.
- Excellent paint-holding capacity on high solids.
- Exceptional value for high volume coating operations.
- Full depth loading. Exclusive design allows paint solids to permeate the blanket from back to front.

SprayStop Polyester Media are designed with multiple fibers and layers to be used in paint overspray applications where process control requires long filter service life, maximum efficiency and air flow, while ensuring maximum production capability.

Applications

- Aerospace
- Furniture Manufacturing
- Automotive Manufacturing
- Appliance Manufacturing
- Automotive Aftermarket
- Contract Coaters

Performance Data

	SprayStop S	SprayStop SHC	SprayStop HCX
Part No. Series	540	541	539
Media Thickness	1"	1"	1.50"
Test Air Flow PM	150	150	150
Initial Resistance on w.g.	.08"	.07"	.03"
Paint Holding Capacity	1478 GM	1677 GM	2628 GM
Rated Removal Efficiency	99.52%	99.73%	99.33%

All information provided from current 40 CFR PART 63 NATIONAL EMISSION STANDARD "6H" Testing.



Paint Type	SprayStop S	SprayStop SHC	SprayStop HCX
Air dry Enamels	GOOD	BEST	BETTER
Stain	GOOD	BEST	BETTER
Lacquers	GOOD	BEST	BETTER
Primers	GOOD	BEST	BETTER
E/S Adhesion Promoters	GOOD	BEST	BETTER
Waterbase	GOOD	BEST	BETTER
Sealers	GOOD	BETTER	BEST
Bake Enamels	GOOD	BETTER	BEST
High Solids	GOOD	BETTER	BEST
Clear Coats	GOOD	BETTER	BEST
Gel Coats	GOOD	BETTER	BEST
Adhesives	GOOD	BETTER	BEST



KOCH FILTER
PURE PERFORMANCE

8401 Air Commerce Drive, Louisville, KY 40219
 toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364
 info@kochfilter.com | www.kochfilter.com