

DuraMAX™ 4vS-16

High Efficiency Synthetic Media Minipleat Filters



Features

- MERV 16 performance rating
- Durable synthetic filter media
- Low resistance to airflow
- Extended filter life
- All-plastic frame construction
- Incinerable

The DuraMAX 4vS-16 is a rigid extended surface air filter engineered to provide maximum performance and prolonged filter lifecycles



Low resistance to airflow and lower energy costs

DuraMAX 4vS-16 provides an unequaled combination of low pressure drop and high efficiency through the use of our unique minipleat design. The **DuraMAX 4vS-16** contains 200 square feet of synthetic filter media in a standard 24x24x12" frame to help insure a low pressure drop, which in turn helps to lower energy costs to the user.

DuraMAX 4vS-16 is constructed with durable, dual-layer synthetic air filter media* designed specifically for high efficiency air filtration applications. The rugged composition of the synthetic media makes the **DuraMAX 4vS-16** an ideal choice for high velocity or high moisture systems, such as Gas Turbines Air Intakes.

DuraMAX filters offer extended filter life

The high capacity minipleat design of the **DuraMAX 4vS-16** insures high dust holding capacity and extended filter lifecycles. Fewer filter changes means reduced disposal costs and lower overall cost of ownership.

DuraMAX filters offer engineered versatility

The **DuraMAX 4vS-16** is designed to meet the wide range of requirements found in today's position of complex air filtration systems. The 4vS is constructed with a durable all-plastic frame that can be completely incinerated. Standard **DuraMAX 4vS-16** filters are UL rated. The **DuraMAX 4vS-16** can be reverse-installed in applications with space limitations.

Nominal	Initial Pressure Drop	Recommended	Media Area
Size	@500 FPM (in. wg.)	Final Pressure Drop	sq. ft.
24x24x12	.43	2.0	200
20x24x12	.43	2.0	164
20x20x12	.43	2.0	136
12x24x12	.43	2.0	98

^{*} Performance and MERV data is based on ASHRAE Test Standard 52.2-2012

^{*}Please see Bulletin No. K-996B for information on our popular original DuraMAX 4v, constructed with microfiberglass.



8401 Air Commerce Drive, Louisville, KY 40219

toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364 info@kochfilter.com | www.kochfilter.com