

Multi-Test Series

Original Equipment Replacement Cartridge



- Fits Aerosolve* original equipment frames
- MERV 7, 12 and 16 performance rating
(ASHRAE Test Standard 52.2-2012)
- Efficiency 55%, 85% and 95%
- Superior dust holding capacity
- High efficiency microfiberglass media

Nominal Size	Efficiency Average Atmospheric			Capacity CFM	Media Area (sq. ft.)	Initial Resistance (in w.g.)			Face Velocity FPM
	MT45	MT85	MT95			MT45	MT85	MT95	
12x24x12 (B)	45-55	80-85	93-97	500	21	0.16	0.25	0.25	250
24x24x12 (A)	45-55	80-85	93-97	1000	43	0.16	0.25	0.25	250
12x24x24 (E)	1200	80-85	450	900	43	0.40	0.45	0.25	450
24x24x24 (D)	1050	80-85	500	1800	86	0.40	0.45	0.25	450

*For Product Identification Purposes Only.

Performance data is based on ASHRAE Test Standards 52.1-1999 and 52.2-2012.



8401 Air Commerce Drive, Louisville, KY 40219
 toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364
 info@kochfilter.com | www.kochfilter.com
 Multi-Test Rigid | Bulletin K-1080-A