

# BioMAX™ 99.99% SBW



## FEATURES:

- Individually Tested Standard Capacity Media
- Particle Board Cell Sides

**DESCRIPTION:** HEPA grade filter with economical particle board sides.

**APPLICATIONS:** Air handlers in medical facilities, pharmaceuticals, clean room manufacturing and indoor gun ranges.

**EFFICIENCY:** 99.99% at 0.3μ

**MEDIA:** Submicron glass fibers formed into a water-resistant, high efficiency high density, wet-laid paper mat.

**RECOMMENDED FINAL PRESSURE DROP:** Consult factory. Rule of thumb is change filter when the initial pressure drop doubles.

**TEMPERATURE:** Maximum continuous operating temperature 180°F (82°C)

**RATINGS:** UL Rated

**PRICE PAGE:** L1-2

See Bulletin No. K-603A for more details

Actual Size W x H x D	Koch Part #	Airflow Capacity (CFM)	Initial Resistance (inches W.G.)	Media Area (sq. ft.)	Efficiency	Shipping Weight (lbs)
24x24x11.50	H66G3X1	1050	1.0	168	99.99 @ 0.3 Micron	40
23.38x23.38x11.50	H64G3X1	1000	1.0	164	99.99 @ 0.3 Micron	38
24x12x11.50	H62G3X1	750	1.0	85	99.99 @ 0.3 Micron	50
12x12x11.50	H61G3X1	525	1.0	32	99.99 @ 0.3 Micron	33
24x18x11.50	H63G3X1	525	1.0	109	99.99 @ 0.3 Micron	33
24x30x11.50	H68G3X1	500	1.0	186	99.99 @ 0.3 Micron	46
24x24x5.88	H16G3X1	550	1.0	77	99.99 @ 0.3 Micron	23
24x12x5.88	H12G3X1	525	1.0	38	99.99 @ 0.3 Micron	24

## Notes:

- All Style SBW BioMAX HEPA filters are furnished with one gasket on the downstream side. If additional gaskets are needed note the location when ordering.
- Contact factory for sizes not listed above. A customer drawing or written submittal is required for all special size filters.