

# Multi-Flo™ MICROFIBERGLASS

Nominal Size W x H x D	Actual Size	NHM No Header Part #	FM Single Header Part #	Airflow Capacity (CFM)	Initial Resistance (inches w.g.)	NHM Media Area (sq. ft.)	SBM/FM Media Area (sq. ft.)
<b>MERV 14 (90-95%)</b>							
24x24x12	23.38x23.38x11.50	112-600-001	112-610-001	2000	.81	61	55
12x24x12	11.38x23.38x11.50	112-600-002	112-610-002	1000	.81	30	24
24x24x6	23.38 x23.38x5.88	112-600-003	112-610-003	1000	.81	33	29
12x24x6	11.38x23.38x5.88	112-600-004	112-610-004	500	.81	16	13
20x20x12	19.38x19.38x11.50	112-600-005	112-610-005	1400	.81	42	37
20x24x12	19.38x23.38x11.50	112-600-006	112-610-006	1667	.81	50	44
20x24x6	19.38x23.38x5.88	112-600-007	112-610-007	834	.81	27	24
20x20x6	19.38x19.38x5.88	112-600-008	112-610-008	700	.81	23	20
<b>MERV 13 (80-85%)</b>							
24x24x12	23.38x23.38x11.50	112-601-001	112-611-001	2000	.71	61	55
12x24x12	11.38x23.38x11.50	112-601-002	112-611-002	1000	.71	30	24
24x24x6	23.38 x23.38x5.88	112-601-003	112-611-003	1000	.71	33	29
12x24x6	11.38x23.38x5.88	112-601-004	112-611-004	500	.71	16	13
20x20x12	19.38x19.38x11.50	112-601-005	112-611-005	1400	.71	42	37
20x24x12	19.38x23.38x11.50	112-601-006	112-611-006	1667	.71	50	44
20x24x6	19.38x23.38x5.88	112-601-007	112-611-007	834	.71	27	24
20x20x6	19.38x19.38x5.88	112-601-008	112-611-008	700	.71	23	20
Nominal Size W x H x D	Actual Size	NHM No Header Part #	FM Single Header Part #	Airflow Capacity (CFM)	Initial Resistance (inches w.g.)	NHM Media Area (sq. ft.)	SBM/FM Media Area (sq. ft.)
<b>MERV 11 (60-65%)</b>							
24x24x12	23.38x23.38x11.50	112-602-001	112-612-001	2000	.49	61	55
12x24x12	11.38x23.38x11.50	112-602-002	112-612-002	1000	.49	30	24
24x24x6	23.38 x23.38x5.88	112-602-003	112-612-003	1000	.49	33	29
12x24x6	11.38x23.38x5.88	112-602-004	112-612-004	500	.49	16	13
20x20x12	19.38x19.38x11.50	112-602-005	112-612-005	1400	.49	42	37
20x24x12	19.38x23.38x11.50	112-602-006	112-612-006	1667	.49	50	44
20x24x6	19.38x23.38x5.88	112-602-007	112-612-007	834	.49	27	24
20x20x6	19.38x19.38x5.88	112-602-008	112-612-008	700	.49	23	20
<b>MERV 10 (40-45%)</b>							
24x24x12	23.38x23.38x11.50	112-603-001	112-613-001	2000	.44	61	55
12x24x12	11.38x23.38x11.50	112-603-002	112-613-002	1000	.44	30	24
24x24x6	23.38 x23.38x5.88	112-603-003	112-613-003	1000	.44	33	29
12x24x6	11.38x23.38x5.88	112-603-004	112-613-004	500	.44	16	13
20x20x12	19.38x19.38x11.50	112-603-005	112-613-005	1400	.44	42	37
20x24x12	19.38x23.38x11.50	112-603-006	112-613-006	1667	.44	50	44
20x24x6	19.38x23.38x5.88	112-603-007	112-613-007	834	.44	27	24
20x20x6	19.38x19.38x5.88	112-603-008	112-613-008	700	.44	23	20

- Average Efficiency: ASHRAE 52.1-1992 and 52.2-2007 test standard • Final Resistance: 1.5" W.G.
- Rated Velocity: 500 FPM - 12" Deep • Rated Velocity: 250 FPM - 6" Deep
- Maximum Operating Temperature: 180 degrees Fahrenheit and 82 degrees Celsius