

# Multi-Sak™ Series S

Nominal Size W x H x D	Koch Part #	Number of Pockets	Airflow Capacity (CFM)	Initial Resistance (IN W.G.)	Recommended Final Presasure Drop (IN. W.G.)
<b>Synthetic MERV 14 (90-95%)</b>					
24x24x36	209-108-136	8	2000	.44	1.50
24x24x30	209-108-130	8	1500	.45	1.50
24x24x22	209-108-122	8	1000	.50	1.50
24x24x18	209-108-118	8	1000	.59	1.50
24x24x36	209-106-136	6	1500	.49	1.50
24x24x30	209-106-130	6	1500	.49	1.50
24x24x22	209-106-122	6	1000	.52	1.50
24x24x18	209-106-118	6	1000	.61	1.50
<b>Synthetic MERV 13 (80-85%)</b>					
24x24x30	208-108-130	8	1500	.36	1.50
24x24x22	208-108-122	8	1000	.44	1.50
24x24x30	208-106-130	6	1500	.40	1.50
24x24x22	208-106-122	6	1000	.46	1.50
<b>Synthetic MERV 11 (60-65%)</b>					
24x24x22	206-108-122	8	1000	.35	1.50
24x24x22	206-106-122	6	1000	.37	1.50
24x24x18	206-106-118	6	1000	.44	1.50
24x24x15	206-106-115	6	1000	.50	1.50

**Notes:**

- Sizes listed above are nominal. Actual face dimensions are -5/8" on length and width. Depth tolerance is ± 1".
- Multi-Sak filters are available with gasketing for side access systems.
- Standard Multi-Sak header thickness is 13/16". 1-1/8" header available.
- Support loops are available on all models.