

Multi-Sak™ Series G

Nominal Size W x H x D	Koch Part #	Number of Pockets	Airflow Capacity (CFM)	Initial Resistance (IN W.G.)	Recommended Final Presasure Drop (IN. W.G.)
Microfiberglass MERV 14 (90-95%)					
24x24x36	219-108-136	8	2000	.46	1.50
24x24x30	219-108-130	8	1500	.47	1.50
24x24x22	219-108-122	8	1000	.52	1.50
24x24x18	219-108-118	8	1000	.61	1.50
24x24x36	219-106-136	6	1500	.51	1.50
24x24x30	219-106-130	6	1500	.51	1.50
24x24x22	219-106-122	6	1000	.54	1.50
24x24x18	219-106-118	6	1000	.63	1.50
Microfiberglass MERV 13 (80-85%)					
24x24x30	218-108-130	8	1500	.38	1.50
24x24x22	218-108-122	8	1000	.46	1.50
24x24x30	218-106-130	6	1500	.42	1.50
24x24x22	218-106-122	6	1000	.48	1.50
Microfiberglass MERV 11 (60-65%)					
24x24x22	216-108-122	8	1000	.37	1.50
24x24x22	216-106-122	6	1000	.39	1.50
24x24x18	216-106-118	6	1000	.46	1.50
24x24x15	216-106-115	6	1000	.51	1.50

Notes:

- Sizes listed above are nominal. Actual face dimensions are -5/8" on length and width. Depth tolerance is ± 1".
- Multi-Sak filters are available with gasketing for side access systems.
- Standard Multi-Sak header thickness is 13/16". 1-1/8" header available.
- Support loops are available on all models.