

Nominal Size (inches)	Actual Size (inches)	Capacity (CFM) @300	Initial Resistance Standard Capacity @300 / 500 FPM	Media Area (in sq. ft.)	Initial Resistance High Capacity @ 300 / 500 FPM	Media Area (in sq. ft.)
12x24x1	11.38 x 23.38 x .75	1000	0.29 @300 FPM	3.3	0.24 @300 FPM	3.8
14x20x1	13.50 x 19.50 x .75	980	0.29 @300 FPM	3.4	0.24 @300 FPM	3.8
14x25x1	13.50 x 24.50 x .75	1215	0.29 @300 FPM	4.3	0.24 @300 FPM	4.8
15x20x1	14.50 x 19.50 x .75	1050	0.29 @300 FPM	3.6	0.24 @300 FPM	4.1
16x20x1	15.50 x 19.50 x .75	1115	0.29 @300 FPM	3.8	0.24 @300 FPM	4.3
16x25x1	15.50 x 24.50 x .75	1400	0.29 @300 FPM	4.8	0.24 @300 FPM	5.4
20x20x1	19.50 x 19.50 x .75	1400	0.29 @300 FPM	4.7	0.24 @300 FPM	5.4
20x24x1	19.50 x 23.50 x .75	1675	0.29 @300 FPM	5.7	0.24 @300 FPM	6.5
20x25x1	19.50 x 24.50 x .75	1740	0.29 @300 FPM	6.0	0.24 @300 FPM	6.8
24x24x1	23.38 x 23.38 x .75	2000	0.29 @300 FPM	7.1	0.24 @300 FPM	8.1
12x24x2	11.38 x 23.38 x 1.75	1000	0.30 @ 500 FPM	5.4	0.27 @ 500 FPM	7.8
14x20x2	13.50 x 19.50 x 1.75	980	0.30 @ 500 FPM	5.5	0.27 @ 500 FPM	7.9
14x25x2	13.50 x 24.50 x 1.75	1215	0.30 @ 500 FPM	6.9	0.27 @ 500 FPM	9.9
15x20x2	14.50 x 19.50 x 1.75	1050	0.30 @ 500 FPM	6.0	0.27 @ 500 FPM	8.4
16x20x2	15.50 x 19.50 x 1.75	1115	0.30 @ 500 FPM	6.5	0.27 @ 500 FPM	8.8
16x25x2	15.50 x 24.50 x 1.75	1400	0.30 @ 500 FPM	8.1	0.27 @ 500 FPM	11.0
18x24x2	17.50 x 23.50 x 1.75	1500	0.30 @ 500 FPM	8.4	0.27 @ 500 FPM	12.3
20x20x2	19.50 x 19.50 x 1.75	1400	0.30 @ 500 FPM	8.0	0.27 @ 500 FPM	11.1
20x24x2	19.50 x 23.50 x 1.75	1675	0.30 @ 500 FPM	9.6	0.27 @ 500 FPM	13.4
20x25x2	19.50 x 24.50 x 1.75	1740	0.30 @ 500 FPM	10.0	0.27 @ 500 FPM	14.0
24x24x2	23.38 x 23.38 x 1.75	2000	0.30 @ 500 FPM	11.4	0.27 @ 500 FPM	16.2
25x25x2	24.50 x 24.50 x 1.75	2170	0.30 @ 500 FPM	12.5	0.27 @ 500 FPM	17.4

Notes:
• MERV (Minimum Efficiency Reporting Value) • Recommended Final Pressure Drop is 1.0" w.g. • Multi-Pleat Elite filters are listed and tested in accordance with UL Standard 900.
• Performance data is based on ASHRAE Test Standard 52.2-2012. • Recommended maximum continuous operational temperature is 150° F.



KOCHFILTER
PURE PERFORMANCE

8401 Air Commerce Drive, Louisville, KY 40219
toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364
info@kochfilter.com | www.kochfilter.com