

Multi-Pleat Green13™

Nominal Size W x H x D	Koch Part #	Height (inches)	Width (inches)	Depth (inches)	Airflow Capacity (@300/500 FPM)	Media Area (sq. ft.)	Resistance @300/500 FPM (inches w.g.)
Standard Capacity Multi-Pleat Green13							
10x20x1	102-714-001	9.50	19.50	.75	425 @300 FPM	2.9	0.31 @300 FPM
12x24x1	102-714-002	11.38	23.38	.75	600 @ 300 FPM	4.2	0.31 @300 FPM
14x20x1	102-714-003	13.50	19.50	.75	590 @300 FPM	4.1	0.31 @300 FPM
14x25x1	102-714-004	13.50	24.508	.75	730 @300 FPM	5.1	0.31 @300 FPM
15x20x1	102-714-005	14.50	19.50	.75	625 @300 FPM	4.4	0.31 @300 FPM
16x20x1	102-714-006	15.50	19.50	.75	670 @300 FPM	4.7	0.31 @300 FPM
16x25x1	102-714-007	15.50	24.50	.75	840 @300 FPM	5.9	0.31 @300 FPM
20x20x1	102-714-008	19.50	19.50	.75	840 @300 FPM	5.9	0.31 @300 FPM
20x25x1	102-714-009	19.50	24.50	.75	1050 @300 FPM	7.4	0.31 @300 FPM
24x24x1	102-714-010	23.38	23.38	.75	1200 @300 FPM	8.5	0.31 @300 FPM
10x20x2	102-714-011	9.50	19.50	1.75	700 @500 FPM	5.6	0.37 @500 FPM
12x24x2	102-714-012	11.38	23.38	1.75	1000 @500 FPM	7.8	0.37 @500 FPM
14x20x2	102-714-013	13.50	19.50	1.75	980 @500 FPM	7.9	0.37 @500 FPM
14x25x2	102-714-014	13.50	24.50	1.75	1215@500 FPM	9.9	0.37 @500 FPM
15x20x2	102-714-015	14.50	19.50	1.75	1050 @500 FPM	8.4	0.37 @500 FPM
16x20x2	102-714-016	15.50	19.50	1.75	1115 @500 FPM	8.8	0.37 @500 FPM
16x25x2	102-714-017	15.50	24.50	1.75	1400 @500 FPM	11.0	0.37 @500 FPM
18x24x2	102-714-018	17.50	23.50	1.75	1500 @500 FPM	12.3	0.37 @500 FPM
20x20x2	102-714-019	19.50	19.50	1.75	1400 @500 FPM	11.1	0.37 @500 FPM
20x24x2	102-714-020	19.50	23.50	1.75	1675 @500 FPM	13.4	0.37 @500 FPM
20x25x2	102-714-021	19.50	24.50	1.75	1740 @500 FPM	14.0	0.37 @500 FPM
24x24x2	102-714-022	23.38	23.38	1.75	2000 @500 FPM	16.2	0.37 @500 FPM
12x24x4	102-714-023	11.38	23.38	3.75	1000 @500 FPM	13.6	0.30 @500 FPM

Nominal Size W x H x D	Koch Part #	Height (inches)	Width (inches)	Depth (inches)	Airflow Capacity (@300/500 FPM)	Media Area (sq. ft.)	Resistance @300/500 FPM (inches w.g.)
Standard Capacity Multi-Pleat Green13							
16x20x4	102-714-025	15.50	19.50	3.75	1111 @500 FPM	13.6	0.30 @500 FPM
16x25x4	102-714-026	15.50	24.50	3.75	1400 @500 FPM	18.1	0.30 @500 FPM
18x24x4	102-714-027	17.50	23.38	3.75	1500 @500 FPM	19.8	0.30 @500 FPM
20x20x4	102-714-028	19.50	19.50	3.75	1400 @500 FPM	18.6	0.30 @500 FPM
20x24x4	102-714-029	19.38	23.38	3.75	1675 @500 FPM	22.3	0.30 @500 FPM
20x25x4	102-714-030	19.50	24.50	3.75	1740 @500 FPM	23.2	0.30 @500 FPM
24x24x4	102-714-031	23.38	23.38	3.75	2000 @500 FPM	26.0	0.30 @500 FPM

Additional Multi-Pleat Green 13 Product Information

- Recommended Final Pressure Drop is 1.0" w.g. • Performance data is based on ASHRAE Test Standards 52.2.2012.
- Recommended maximum continuous operational temperature is 200° F (93°C).
- Multi-Pleat Green 13 filters are listed and tested in accordance with UL Standard 900.