

Nominal Size (inches)	Actual Size (inches)	Capacity (CFM)		Initial Resistance (in. W.G.)		Media Area
		@300 FPM	@500 FPM	@300 FPM	@500 FPM	
16x20x1	15.5 x 19.5x.75	650	815	0.50	NA	4.8
16x25x1	15.5 x 24.5 x .75	850	1060	0.50	NA	56.0
20x20x1	19.5 x 19.5 x .75	850	1060	0.50	NA	6.2
20x25x1	19.5 x 24.5 x .75	1050	1315	0.50	NA	7.7
24x24x1	23.38 x 23.38 x .75	1200	1500	0.50	NA	8.6
12x24x1	11.38 x 23.38 x .75	600	750	0.50	NA	4.2
16x20x2	15.5 x 19.5 x 1.75	650	1085	0.20	0.43	8.3
16x25x2	15.5 x 24.5 x 1.75	850	1420	0.20	0.43	10.5
20x20x2	19.5 x 19.5 x 1.75	850	1420	0.20	0.43	11.2
20x25x2	19.5 x 24.5 x 1.75	1050	1755	0.20	0.43	13.1
24x24x2	23.38 x 23.38 x 1.75	1200	2000	0.20	0.43	15.0
12x24x2	11.38 x 23.38 x 1.75	600	1000	0.20	0.43	7.5
16x20x4	15.5 x 19.5 x 3.63	650	1085	0.18	0.40	15.1
16x25x4	15.5 x 24.5 x 3.63	850	1420	0.18	0.40	18.9
20x20x4	19.5 x 19.5 x 3.63	850	1420	0.18	0.40	19.4
20x25x4	19.5 x 24.5 x 3.63	1050	1755	0.18	0.40	24.2
24x24x4	23.38 x 23.38 x 3.63	1200	2000	0.18	0.40	27.0
12x24x4	11.38 x 23.38 x 3.63	600	1000	0.18	0.40	12.9

Notes:

- MERV (Minimum Efficiency Reporting Value) • Recommended Final Pressure Drop is 1.0" w.g.
- Performance data is based on ASHRAE Test Standards 52.2.2012 • Recommended maximum continuous operational temperature is 500° F.



8401 Air Commerce Drive, Louisville, KY 40219
toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364
info@kochfilter.com | www.kochfilter.com