

Duo-Cube Technical Data and Performance Specifications

Nominal Size	Capacity (CFM)	Media Area (Sq. Ft.)	Initial Resistance (In. W.G.)			
			1 Ply	2 Ply	3 Ply	4 Ply
16x20x8	800	6.2	.10	.13	.15	.16
16x25x8	1000	7.3	.10	.13	.15	.16
20x20x8	1000	7.2	.10	.13	.15	.16
20x25x8	1200	7.8	.10	.13	.15	.16
24x24x8	1500	9.3	.10	.13	.15	.16
16x20x11	1000	7.7	.15	.20	.22	.24
16x25x11	1300	9.0	.15	.20	.22	.24
20x20x11	1300	8.9	.15	.20	.22	.24
20x25x11	1500	11.4	.15	.20	.22	.24
24x24x11	1700	11.3	.15	.20	.22	.24
16x20x15	1100	9.7	.19	.26	.29	.32
16x25x15	1400	11.3	.19	.26	.29	.32
20x20x15	1400	11.1	.19	.26	.29	.32
20x25x15	1750	12.9	.19	.26	.29	.32
24x24x15	2000	14.0	.19	.26	.29	.32
16x20x20	1800	12.2	.23	.31	.35	.38
16x25x20	2000	14.2	.23	.31	.35	.38
20x20x20	2000	13.9	.23	.31	.35	.38
20x25x20	2300	16.0	.23	.31	.35	.38

Performance data is based on ASHRAE Test Standards 52.1-1999 and 52.2-2007.



KOCH FILTER
PURE PERFORMANCE

8401 Air Commerce Drive, Louisville, KY 40219
toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364
info@kochfilter.com | www.kochfilter.com