

Nominal Size	Actual Size	Capacity (CFM)			Initial Resistance (In. W.G.)									Final Resistance	Media Area (sq. ft.)
		@300 FPM	@500 FPM	@625 FPM	@300 FPM MERV			@500 FPM MERV			@625 FPM MERV				
					8	11	13	8	11	13	8	11	13		
24x24x2	23.38x23.38x1.75	1200	2000	2500	.13	.15	.13	.23	.32	.30	.33	.52	.42	1.0	16.2
12x24x2	11.38x23.38x1.75	600	1000	1250	.13	.15	.13	.23	.32	.30	.33	.52	.42	1.0	7.8
20x20x2	19.50x19.50x1.75	840	1400	1740	.13	.15	.13	.23	.32	.30	.33	.52	.42	1.0	11.1
20x25x2	19.50x24.50x1.75	1050	1740	2170	.13	.15	.13	.23	.32	.30	.33	.52	.42	1.0	14.0
16x25x2	15.50x24.50x1.75	840	1400	1740	.13	.15	.13	.23	.32	.30	.33	.52	.42	1.0	11.0
16x20x2	15.50x19.50x1.75	670	1115	1400	.13	.15	.13	.23	.32	.30	.33	.52	.42	1.0	8.8
20x24x2	19.50x23.38x1.75	1000	1675	2100	.13	.15	.13	.23	.32	.30	.33	.52	.42	1.0	13.4
24x24x4	23.38x23.38x3.75	1200	2000	2500	.11	.14	.12	.21	.30	.28	.31	.46	.40	1.0	26.0
12x24x4	11.50x23.38x3.75	600	1000	1250	.11	.14	.12	.21	.30	.28	.31	.46	.40	1.0	13.6
20x20x4	19.50x19.50x3.75	840	1400	1740	.11	.14	.12	.21	.30	.28	.31	.46	.40	1.0	18.6
20x24x4	19.50x23.38x3.75	1000	1675	2100	.11	.14	.12	.21	.30	.28	.31	.46	.40	1.0	22.3

Additional Multi-Pleat BOSS Product Information:

- MERV (Minimum Efficiency Reporting Value) • Recommended Final Pressure Drop is 1.0" w.g. • Performance data is based on ASHRAE Test Standards 52.2-2012
- Recommended maximum continuous operating temperature is 200°F



KOCHFILTER
PURE PERFORMANCE

8401 Air Commerce Drive, Louisville, KY 40219
toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364
info@kochfilter.com | www.kochfilter.com