

# Multi-Pleat™ XL10

## MERV 10 Extended Surface Pleated Panel Filter



### FEATURES

Upgrade from standard pleated filter

MERV 10 efficiency

Low resistance to airflow

High dust holding capacity

Sturdy double-wall frame design

Moisture resistant beverage board frame

### Multi-Pleat XL10

The Koch Multi-Pleat XL10 is a medium efficiency extended surface pleated panel filter, engineered to provide higher initial efficiencies and overall superior performance than MERV 8 pleated filters. The Multi-Pleat XL10 has an efficiency of MERV 10 when tested in accordance with ASHRAE Test Standard 52.2-2017.

The efficiency provided by the Multi-Pleat XL10 makes the filter an excellent upgrade from disposable filters and standard MERV 6, 7 and 8 pleated filters. The Multi-Pleat XL10 is an ideal selection in applications such as hospitals, laboratories, pharmaceutical applications, commercial office buildings and systems to improve indoor air quality and to extend the life of final higher efficiency filters.

### Multi-Pleat XL10 Construction


The Multi-Pleat XL10 media is produced with a blend of highly specialized fibers, developed by Koch Filter specifically for use in extended surface air filters. Developed to deliver balanced performance, this specialized media utilizes mechanical filtration principles to provide high efficiency, low pressure drop and high dust holding capacity.

Standard capacity XL10 filters provide a combination of efficiency, economy, and excellent overall performance. Standard capacity XL10 filters are an excellent choice in applications where filter change schedules are based on preventive maintenance schedules.


## Multi-Pleat™ XL10 Performance Data

Filter Depth	Air Velocity	Initial Resistance (inches w.g.)	Final Resistance (inches w.g.)	Pleats Per Linear Foot
1"	300 FPM	0.15	1.0	13
2"	500 FPM	0.27	1.0	10
4"	500 FPM	0.18	1.0	9

## Initial Resistance vs. Air Flow Rate



## Efficiency by Particle Size



## Multi-Pleat™ XL10 Specifications

Specifications	
Filter Depth	1", 2" 4" and 6"
Efficiency	MERV 10
Media	100% Synthetic
Media Support	Expanded Metal on Downstream Side
Frame Type	Beverage Board
Max Operating Temperature	200°F (93°C)
Recommended Final Resistance	1" w.g.
Filter Certification	UL 900 and ULC-S111-07
Manufacturing Certification	ISO 9001:2015

## Engineering Specifications

### 1.0 General Specifications

- 1.1 Filters shall be Multi-Pleat XL10 extended surface pleated air filters as manufactured by Koch Filter.
- 1.2 Filters shall be available in nominal depths of 1", 2", 4" and 6", in standard and high capacity configurations.
- 1.3 Filters are classified by Underwriters Laboratories to UL 900 and ULC-S111-07.
- 1.4 Filters are manufactured by an ISO 9001 registered company.

### 2.0 Filter Material and Construction

- 2.1 Media shall be 100% synthetic media.
- 2.2 Filters shall have an expanded galvanized steel support grid bonded to the air-exiting side of the filter to maintain pleat uniformity and prevent fluttering.
- 2.3 Filter frame shall be comprised of a high wet strength beverage board with a cross member designed to increase filter strength and rigidity. Frame shall be recyclable.

### 3.0 Filter Performance

- 3.1 Filters shall be MERV 10 in standard capacity and high capacity configurations and when tested in accordance with ASHRAE 52.2 Test Standard.
- 3.2 For initial resistance of filters, see Performance Data chart above.
- 3.3 Filters shall be rated to withstand a continuous operating temperature up to 200°F.
- 3.4 Filters shall have a recommended final resistance of 1.0" w.g.

Part Number	Nominal Size*	Capacity (CFM)	
	WxHxD	300 FPM	500 FPM
102-111-020	10x10x1	200	350
102-380-001	10x20x1	425	700
102-380-051	12x12x1	300	500
102-111-001	12x18x1	450	750
102-111-002	12x20x1	500	850
102-380-002	12x24x1	600	1000
102-111-003	12x25x1	625	1050
102-380-003	14x20x1	575	986
102-111-005	14x24x1	700	1175
102-380-004	14x25x1	725	1225
102-111-039	14x30x1	875	1450
102-380-005	15x20x1	625	1050
102-111-006	15x25x1	775	1300
102-111-007	16x16x1	550	900
102-380-006	16x20x1	675	1125
102-111-008	16x24x1	800	1350
102-380-007	16x25x1	850	1400
102-111-018	16x30x1	1000	1675
102-111-009	18x18x1	675	1125
102-111-015	18x20x1	750	1250
102-111-016	18x24x1	900	1500
102-111-011	18x25x1	950	1575
102-111-044	18x30x1	1125	1875
102-380-008	20x20x1	850	1400
102-111-049	20x22x1	900	1525
102-111-017	20x24x1	1000	1675
102-380-009	20x25x1	1000	1750
102-111-012	20x30x1	1250	2100
102-380-010	24x24x1	1200	2000
102-111-013	24x30x1	1500	2500
102-111-014	25x25x1	1300	2175
Part Number	WxHxD	300 FPM	500 FPM
102-380-011	10x20x2	700	875
102-112-035	12x12x2	500	625
102-112-002	12x20x2	850	1050
102-380-012	12x24x2	1000	1250
102-112-003	12x25x2	1050	1300
102-380-013	14x20x2	975	1225
102-380-014	14x25x2	1225	1525
102-112-039	14x30x2	1450	1825
102-380-015	15x20x2	1050	1300
102-112-005	16x16x2	900	1125
102-380-016	16x20x2	1125	1400
102-380-053	16x24x2	1350	1675
102-380-017	16x25x2	1400	1750
102-112-018	16x30x2	1675	2100
102-112-007	18x18x2	1125	1400
102-112-015	18x20x2	1250	1575
102-380-018	18x24x2	1500	1875
102-112-009	18x25x2	1575	1950
102-380-019	20x20x2	1400	1750
102-380-020	20x24x2	1675	2100
102-380-021	20x25x2	1750	2175
102-112-010	20x30x2	2100	2600
102-112-030	20x35x2	2450	3050
102-380-022	24x24x2	2000	2500
102-112-011	24x30x2	2500	3125
102-380-050	25x25x2	2175	2725
Part Number	WxHxD	300 FPM	500 FPM
102-380-023	12x24x4	1000	1250
102-380-024	15x20x4	1050	1300
102-380-025	16x20x4	1125	1400
102-114-005	16x24x4	1350	1675
102-380-026	16x25x4	1400	1750
102-380-027	18x24x4	1500	1875
102-380-028	20x20x4	1400	1750
102-380-029	20x24x4	1675	2100
102-380-030	20x25x4	1750	2175
102-380-031	24x24x4	2000	2500
102-114-010	25x29x4	2525	3150
102-380-041	24x24x6	2000	2500